

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Caniprevent

UFI: Q72G-FVC9-QVJG-5VET

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Dr. Windmann Pharma GmbH & Co. KG	
Street:	Otto-Hahn-Straße 19	
Place:	D-26810 Westoverledingen	
Telephone:	+4955 987 990 0	
E-mail:	info@windmann-pharma.de	
Contact person:	Sievert Julius Windmann	Telephone: +4955 987 990 0
E-mail:	info@windmann-pharma.de	

1.4. Emergency telephone number:

Tel: +49 1575 2089788 (24 Std.)

Further Information

No information available.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Warning

Pictograms:



Hazard statements

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370+P378	In case of fire: Use sand, extinguishing powder or alcohol-resistant foam to extinguish.

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 2 of 13

P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria. This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Vapours can form explosive mixtures with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			20 - < 25 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	20 - < 25 %
	inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 12800-13400 mg/kg; oral: LD50 = 5045 mg/kg		

Further Information

No information available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Provide fresh air.
Remove contaminated, saturated clothing immediately.
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

If unconscious but breathing normally, place in recovery position and seek medical advice.

After contact with skin

Remove contaminated, saturated clothing immediately.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
In case of skin irritation, consult a physician.

After contact with eyes

Protect uninjured eye. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 3 of 13

After ingestion

Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Let water be drunken in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

propan-2-ol; isopropyl alcohol; isopropanol: Risk of respiratory paralysis.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO₂), Water spray jet, alcohol resistant foam.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Closed containers may burst when pressure and temperature rise

Do not inhale explosion and combustion gases.

In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for firefighters Flame-retardant protective clothing, Full protection suit

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Dispose of waste according to applicable legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

See protective measures under point 7 and 8.

Wear personal protection equipment (refer to section 8).

Provide adequate ventilation.

Do not breathe gas/fumes/vapour/spray.

Remove all sources of ignition.

Take precautionary measures against static discharges.

Use only antistatically equipped (spark-free) tools. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment.

Avoid contact with skin, eyes and clothes.

Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Keep away from unprotected people.

For emergency responders

Suppress gases/vapours/mists with water spray jet.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

Do not allow to enter into soil/subsoil.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 4 of 13

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Unsuitable material for taking up: Combustible substance

Treat the recovered material as prescribed in the section on waste disposal.

Use only antistatically equipped (spark-free) tools. Ground and bond container and receiving equipment.

For cleaning up

Water (with cleaning agent)

Retain contaminated washing water and dispose it.

Other information

Provide fresh air.

6.4. Reference to other sections

See protective measures under point 7 and 8.

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

See section 8.

Wear personal protection equipment (refer to section 8).

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Provide adequate ventilation.

In case of inadequate ventilation wear respiratory protection.

Keep container tightly closed. Always close containers tightly after the removal of product.

Avoid contact with eyes and skin.

Avoid release to the environment. Clear spills immediately.

Floors, walls and other surfaces in the hazard area must be cleaned regularly.

Clear lines prior to de-coupling.

Advice on protection against fire and explosion

Vapours can form explosive mixtures with air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

Use only antistatically equipped (spark-free) tools.

Provide earthing of containers, equipment, pumps and ventilation facilities.

Advice on general occupational hygiene

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Work in well-ventilated zones or use proper respiratory protection.

Only wear fitting, comfortable and clean protective clothing.

Avoid contact with eyes and skin.

Wash hands before breaks and after work.

Do not put any product-impregnated cleaning rags into your trouser pockets.

Take off contaminated clothing and wash it before reuse.

When using do not eat, drink, smoke, sniff.

Keep away from sources of ignition - No smoking.

Make available sufficient washing facilities Provide eye shower and label its location conspicuously

Further information on handling

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Observe instructions for use.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 5 of 13

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

Protect against heat and direct sunlight.

Ensure adequate ventilation of the storage area.

The floor should be leak tight, jointless and not absorbent. Material, solvent-resistant

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Strong acid, Alkali (lye), Oxidizing agent

Further information on storage conditions

Avoid: Heat, Frost, Humidity

storage temperature: 5-20°C

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Worker DNEL, acute		inhalation	systemic	1000 mg/m³
Consumer DNEL, acute		inhalation	systemic	178 mg/m³
Consumer DNEL, acute		oral	systemic	51 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	500 mg/m³
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m³
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
56-81-5	Glycerol			
Worker DNEL, long-term		inhalation	local	56 mg/m³
Consumer DNEL, long-term		inhalation	local	33 mg/m³
Consumer DNEL, long-term		oral	systemic	229 mg/kg bw/day

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 6 of 13

PNEC values

CAS No	Substance	
Environmental compartment		Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg
56-81-5	Glycerol	
Freshwater		0,885 mg/l
Freshwater (intermittent releases)		8,85 mg/l
Marine water		0,088 mg/l
Freshwater sediment		3,3 mg/kg
Marine sediment		0,33 mg/kg
Micro-organisms in sewage treatment plants (STP)		1000 mg/l
Soil		0,141 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaust at critical locations. Use only outdoors or in a well-ventilated area. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Provide earthing of containers, equipment, pumps and ventilation facilities.

Provide earthing of containers, equipment, pumps and ventilation facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. EN 166

Tightly sealed safety glasses. goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: $\geq 0,5$ mm

Breakthrough time: ≥ 480 min

Thickness of the glove material, Breakthrough times and swelling properties of the material must be taken into consideration. Observe the wear time limits as specified by the manufacturer.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Check leak tightness/impermeability prior to use.

Skin protection

DIN EN 340

Chemical resistant safety shoes

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 7 of 13

Wear suitable protective clothing. (antistatic, flame-retardant, liquid-tight, solvent-resistant)

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values, Aerosol-/ Generation/formation of dust
Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Combination filtering device Type A-P1 Full-/half-/quarter-face masks (EN 136/140)

Thermal hazards

Vapours can form explosive mixtures with air.

Environmental exposure controls

Provide for retaining containers, e.g. floor pan without outflow.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
		Test method
Melting point/freezing point:	No data available	
Boiling point or initial boiling point and boiling range:	82,5 °C *	
Flammability:	No data available	
Lower explosion limits:	2 vol. %	
Upper explosion limits:	13 vol. %	
Flash point:	26,5 °C	DIN EN ISO 3679
Auto-ignition temperature:	not applicable	
Decomposition temperature:	No data available	
pH-Value:	5,5	
Viscosity / kinematic:	No data available	
Water solubility:	partially soluble	
Solubility in other solvents		
No information available.		
Partition coefficient n-octanol/water:	No data available	
Vapour pressure:	60,2 hPa *	
(at 20 °C)		
Vapour pressure:	No data available	
Density (at 20 °C):	0,96 g/cm ³	
Bulk density:	No data available	
Relative vapour density:	No data available	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No information available.

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 8 of 13

Solvent content: 20,00 %, Water, demineralized: 69,90 %
Solid content: 0%
Sublimation point: No data available
Softening point: No data available
Pour point: No data available
Viscosity / dynamic: No data available
Flow time: No data available

Further Information

* calculated.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

Reaction with: Oxidizing agent, Acids

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong acid, Alkali (lye), Oxidizing agent

10.6. Hazardous decomposition products

Reference to other sections: 5

Further information

No information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 5045 mg/kg	Rat		
	dermal	LD50 12800-13400 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 30 mg/l	Rat		

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 9 of 13

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

Further information

The product has not been tested.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	REACH Registration Dossier
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Desmodesmus subspicatus	
	Acute crustacea toxicity	EC50 mg/l	13299	48 h	Daphnia magna (Big water flea)	
	Fish toxicity	NOEC mg/l	> 1000	28 d	Danio rerio	REACH Registration Dossier
	Crustacea toxicity	NOEC mg/l	> 1000	21 d	Daphnia magna	REACH Registration Dossier
						other: REACH Guidance on QSARs R.6
						other: REACH Guidance on QSARs R.6

12.2. Persistence and degradability

No further relevant information available.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
	OECD 301E	95%	21	

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 10 of 13

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

BCF

CAS No	Chemical name	BCF	Species	Source
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,994		Meylan,WM, Howard,PH

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

-

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

water hazard class 1

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Hazardous waste according to Directive 2008/98/EC (waste framework directive).
packaging: Do not pierce or burn, even after use.

List of Wastes Code - residues/unused products

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08);
waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Uncleaned empty containers may contain product gases which form explosive mixtures with air.

Completely emptied packages can be recycled. Packing which cannot be properly cleaned must be disposed of. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 11 of 13

Classification code: F1
Special Provisions: 274 601
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Classification code: F1
Special Provisions: 274 601
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (propan-2-ol; isopropyl alcohol; isopropanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Special Provisions: 223 274 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3
Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

Other applicable information

No information available.

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 12 of 13

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: 28,5 % (273,6 g/l)

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)
Classification according to Regulation (EC) No 1272/2008 [CLP]
COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
Classification according to Regulation (EC) No 1272/2008 [CLP]
DIRECTIVE (EU) 2018/851 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 30 May 2018 amending Directive 2008/98/EC on waste
DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 19 November 2008 on waste and repealing certain Directives

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Germany:
TRGS 201, TRGS 220, TRGS 400, TRGS 401, TRGS 402, TRGS 500, TRGS 509, TRGS 510, TRGS 555, TRGS 720ff., TRGS 800, TRGS 900
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV)
Hazardous Substances Ordinance (GefStoffV)
Dangerous Goods Ordinance for Road, Rail and Inland Navigation (GGVSEB)
Dangerous Goods Officer Ordinance (GbV)

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:
propan-2-ol; isopropyl alcohol; isopropanol

SECTION 16: Other information

Safety Data Sheet

Caniprevent

Revision: 27.11.2025

Page 13 of 13

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
Flam. Liq. 3: Flammable liquids, hazard category 3
Eye Irrit. 2: Eye irritation, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer
(Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
CAS: Chemical Abstracts Service (division of the American Chemical Society)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
EC50: Effective concentration, 50 percent
DNEL: Derived No Effect Level
PNEC: Predicted No Effect Concentration
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

Key literature references and sources for data

ECHA, GESTIS, SDB Supplier

Classification for mixtures and used evaluation method

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)